

training—numerical optimization—and report on the results of some preliminary tests in training rule bases. They also show that truth maintenance can be used to make the training more efficient and ask some epistemological questions raised by training rule weights.

A Study of Associative Evidential Reasoning

Yizong Cheng

*Department of Computer Science, University of Cincinnati,
Cincinnati, Ohio 45221*

Rangasami L. Kashyap

*School of Electrical Engineering, Purdue University, West
Lafayette, Indiana 47906*

Evidential reasoning is cast as the problem of simplifying the evidence-hypothesis relation and constructing combination formulas that possess certain testable properties. Important classes of evidence as identifiers, annihilators, and idempotents and their roles in determining binary operations on intervals of reals are discussed. The appropriate way of constructing formulas for combining evidence and their limitations—for instance, in robustness—are presented.

Address correspondence to Y. Cheng.

Stochastic Simulation of Bayesian Belief Networks

Homer L. Chin and Gregory F. Cooper

*Medical Computer Science Group, Knowledge Systems
Laboratory, Medical School Office Building, Room 215, Stanford
University Medical Center, Stanford, California 94305*

This paper examines the use of stochastic simulation of Bayesian belief networks as a method for computing the probabilities of values of variables. Specifically, it examines the use of a scheme described by Henrion, called logic sampling, and an extension to that scheme described by Pearl. The scheme devised by Pearl allows us to “clamp” any number of variables to given values and to conduct stochastic simulation on the resulting network. This algorithm, in certain networks, leads to much slower than expected convergence to the true posterior probability. This behavior is a result of the tendency for local areas in the graph to become fixed through many stochastic iterations. The length of this nonconvergence can be made arbitrarily long by strengthening the dependency between two nodes. This paper describes the use of graph modification. By modifying a belief network through the use of pruning, arc reversal, and node reduction, it may be possible to convert the network to a form that is computationally more efficient for stochastic simulation.

Address correspondence to H. L. Chin.